

GATEWAY

G2

User Manual

GATEWAY G2

Model :	G2
Dimensions :	70mm x 70mm x 26mm
Network :	WiFi 2.4G
IEEE standard :	802.11 b/g/n
Power interface :	Type-C USB
Power input :	DC 5V/500mA

Light Status




When the gateway is powered on:

- Light flashes alternately in red and blue: Stand-by mode, ready for pairing
- Blue light: Working mode
- Red light: Network failure

Pair the Gateway with APP

1 Activate the APP



2 Press "☰"




3 Select [Gateway]




4 Select [G2]



5 Plug in the gateway and power it on, while the light flashes alternately in red and blue



6 Press "+" sign



7 Add Gateway



8 Select the network and fill in the password



9 Add complete

⚠ Notice: If times out, please power off and try it again.

GATEWAY

G2

Manual

GATEWAY G2

Model:	G2
Mål:	70mm x 70mm x 26mm
Netværk:	WiFi 2.4G
IEEE standard:	802.11 b/g/n
Strømgrænseflade:	Type-C USB
Strømindgang:	DC 5V/500mA

Lysindikator




Når gatewayen er tændt:

- Lys blinker skiftevis i rødt og blåt:
Standby-tilstand, klar til parring
- Blåt lys: Arbejdstilstand
- Rødt lys: Netværksfejl

Par gatewayen med APP

1 Åben TLock APP




2 Klik på ☰




3 Vælg [Gateway]




4 Vælg [G2]



5 Tilslut gatewayen og tænd den, mens lyset blinker skiftevis i rødt og blåt



6 Klik på "+"-tegnet



7 Tilføj gateway



8 Vælg netværket, og udfyld adgangskoden



9 Tilføje af gateway gennemført

⚠ Bemærk: Hvis timeout, sluk venligst og prøv igen